SERIE / RANGE **VE**



VE38D



VE50D



VE65D

TIPO *TYPE*	Ø mm	VIBRAZIONI *VIBRATIONS* min.	ASSORBIMENTO A CARICO *LOADED AMPERAGE* 230 V 50/60 Hz	FORZA CENTRIFUGA *CENTRIFUGAL FORCE*	TUBO DI MANOVRA *HOSE LENGHT*	CAVO ELETTRICO *ELECTRICAL CABLE*	PESO *WEIGHT*	SENZA TERMICA *WITHOUT THERMAL PROTECTION*	CON TERMICA *WITH THERMAL PROTECTION*
VE38D	38	12.000	A 1,5	N 1.700	MT. 5	MT. 10	Kg. 14	✔	
VE50D	50	12.000	A 2,5	N 3.800	MT. 5	MT. 10	Kg. 20		✔
VE60D	60	12.000	A 3	N 5.700	MT. 5	MT. 10	Kg. 23		✔
VE65D	65	12.000	A 4,5	N 7.300	MT. 5	MT. 10	Kg. 25		✔

CARATTERISTICHE TECNICHE PULSANTIERA ELETTRONICA
ELECTRONIC CONTROL TECHNICAL SPECIFICATIONS



Tensione di alimentazione / Input voltage	230 V 50-60 Hz
Corrente massima assorbita / Maximum current input	10 A
Temperatura di esercizio / Operating temperature	-10°C +40°C
Tensione d'uscita / Output voltage	230 V. 200Hz
Potenza massima / Maximum power	2000 VA
Ingombro / Dimensions	330x100x90 mm.
Peso / Weight	2 Kg
Protezioni / Protections:	
Corto circuito / Short circuit	10 A
Massimo carico / Maximum load	8 A
Protezione termica / Thermal protection	85°C
Minima tensione / Undervoltage	165 Vac
Massima tensione / Maximum voltage	275 Vac

VIBRATORI ELETTRONICI CON CONVERTITORE INCORPORATO VE

UTILIZZO: compattazione del calcestruzzo

CARATTERISTICHE

TESTINA/PUNTALE: in acciao cementato, a richiesta con gomma

"BOTTIGLIA": statore potenziato e sovradimensionato con termica, n° 4 cuscinetti di marche primarie;

CERTIFICAZIONI: a norma CE, secondo le direttive comunitarie e successive modifiche: 2006/42/CE | 206/95/CE

VE ELECTRONIC VIBRATORS WITH INCORPORATED CONVERTER

APPLICATION: concrete compaction

CHARACTERISTICS

END CAP: with cemented steel, on request with rubber cap

"BOTTLE": stator enhanced and oversized with thermal protection, n° 4 bearings of main brands

CERTIFICATIONS: EC normative, Comunity Directive and subsequent modifications: 2006/42/EC | 206/95/EC